

















CERTIFICATION AND CLASSIFICATION		STANDARD	ModularT 7
Type of flooring		ISO (EN) 10582	Compact resilient floor covering
CE certification		EN 14041	 YES
Classification	ISO 10874 (EN 685)	  	Residential: 23 Commercial: 34 Industrial: 43
TECHNICAL CHARACTERISTICS		STANDARD	ModularT 7
Total thickness		ISO 24346 (EN 428)	 2,5 mm
Wear layer thickness		ISO 24340 (EN 429)	 0,7 mm
Bevelled edges			YES
Total weight		ISO 23997 (EN 430)	 3200 g/m ²
Abrasion (wear layer binder content)		ISO 10582	Type I
Form of delivery	ISO 24342 (EN 427)		Plank 20 x 120 cm, 18 planks/box = 4,32m ² Tiles 60 x 60 cm, 12 tiles/box = 4,32m ² Tiles 66,5 x 66,5 cm, 10 tiles/box = 4,42m ² Tiles 50 x 100 cm, 8 tiles/box = 4 m ²
TECHNICAL PERFORMANCES		STANDARD	ModularT 7
Dimensional stability		ISO 23999 (EN 434)	 ≤ 0.10 %
Reaction to fire		EN 13501-1	 Bfls1 on concrete substrate
Residual indentation		ISO 24343-1(EN 433)	 ≤ 0,10 mm
Furniture leg		EN 424	 No damage
Castor chair		ISO 4918 (EN 425)	 No damage
Curl resultant to heat		ISO 23999 (EN 434)	≤ 2 mm
Thermal resistance		ISO (EN) 12524	 0,02 - 0,03 m ² K/W
Acoustic insulation		ISO (EN) 717/2	 6 dB
Walking noise		NF S 31- 074	L n,e,w = 76 dB
Light fastness		ISO (EN) 105-B02	 7/8
Slip resistance		EN 13893 DIN 51130	 μ ≥ 0,3 R9/R10 depending on embossing type
Electrical properties		EN 1815 EN 1081	≤ 2 kV ≤ 1*10 ⁹ Ohm

