

# Salsa Premium

2020

WOOD  
product  
data  
sheet



pattern: 3strip

The natural beauty of these designs, with emphasized wood grain and warm colors.

board size: 2283 x 194 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	oil color	surface oil	gloss level	brushed	heat treatment	bevel	dop number
Essential Pure / Antique White, Grey	550170002	OAK MOONSTONE BR	Oak	Nature	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Classic / Beige	550170003	ASH QUARTZ BR	Ash	Nature	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Classic / Beige	550170004	OAK JASPER BR	Oak	Original	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Brown/ Mocha	550170006	OAK TOPAZ BR	Oak	Nature	No	transparent	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Pure / White	550170008	ASH CRYSTAL BR	Ash	Nature	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Brown / Mocha	550170014	OAK GINGER BR	Oak	Original	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08
Essential Brown / Cocoa	550170015	OAK BRONZITE BR	Oak	Rustic	No	Yes	PHO	-	Yes	No	No	2702-0005-DoP-2015-08

PHO - Proteco Hardwax Oil

## installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.

## maintenance

- The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1 – WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth. Use protective pads when moving furniture
- 2 – DRY CLEANING: Dry mopping & vaccum cleaning
- 3 – REGULAR CLEANING: Osmo Wash and Care
- 4 – OCCASIONAL INTENSIVE CLEANING: Osmo Liquid Wax Cleaner
- 5 – PROTECTION PRESERVATION AND RENEWAL: Osmo Polyx®-Oil



**T-LOCK**  
Tarkett lock, glue-free locking system

**AQUA GUARD**  
Extended liquid resistance at the short side of boards connection

**HEALTHY FLOORS**  
Lacquer properties prevent bacteria reproduction

**ENVIRONMENTAL COMMITMENT**  
Environmental responsibility throughout all processes ( C2C, FSC, ISO14001)

**WARRANTY**  
30 years residential warranty



# underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

\*Not suitable for the wood species beech and maple

## technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m <sup>3</sup>	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

## size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	194
Length (mm)	2283
Wear layer thickness (mm)	~3,6
Boards/pack	6
m <sup>2</sup> /pack	2,658
m <sup>2</sup> /pallet	132,9
Weight/m <sup>2</sup> (kg)	~7,15

## design overview



ASH CRYSTAL BR

OAK MOONSTONE BR

OAK JASPER BR

OAK TOPAZ BR

ASH QUARTZ BR

OAK GINGER BR



OAK BRONZITE BR