

Samba

2020

WOOD
product
data
sheet



pattern: 3strip

Samba designs are simple solution for every taste due to variety of natural lines!

board size: 1123 x 194 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Brown / Cognac	550051028	ASH SMOKED	Ash	Robust	No	Yes	CL	30	No	Yes	No	2702-0005-DoP-2015-08
Essential Classic / Nature	550051038	OAK NATURE	Oak	Nature	No	No	CL	30	No	No	No	2702-0005-DoP-2015-08
Essential Pure / Ivory, Grey	550051039	OAK CREAM	Oak	Nature	No	Yes	CL	30	No	No	No	2702-0005-DoP-2015-08
Essential Brown / Cognac	550051026	AFRICAN MAHOGANY	A. Mah.	Robust	No	Yes	CL	30	No	No	No	2702-0005-DoP-2015-08
Essential Classic / Honey	550051035	OAK BRANDY	Oak	Original	No	Yes	CL	30	No	No	No	2702-0005-DoP-2015-08
Essential Brown/Brown Mocha	550051036	OAK ANTIQUE	Oak	Original	No	Yes	CL	30	No	No	No	2702-0005-DoP-2015-08
Art Fashion / Rustic Art	550051046	ASH BRANDY	Ash	Rustic	Yes	No	CL	30	No	No	No	2702-0005-DoP-2015-08
Essential Classic / Beige	550051047	OAK ARCTIC BR HG	Oak	Nature	No	Yes	CL (HG)	70	Yes	No	No	2702-0005-DoP-2015-08
Essential Brown / Cocoa	550051049	ASH COCOA BR	Ash	Robust	No	Yes	CL	30	Yes	No	No	2702-0005-DoP-2015-08
Vintage / Vintage Dark	550051065	OAK GRAPHITE BR	Oak	Rustic	Yes	No	CL	30	Yes	No	No	2702-0005-DoP-2015-08

CL - Classic Lacquer CL(HG) - Classic Lacquer High Gloss

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.

maintenance

- The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1— WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth.
Use protective pads when moving furniture
- 2— DRY CLEANING: Dry mopping& vaccum cleaning



T-LOCK
Tarkett lock, glue-free locking system

AQUA GUARD
Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS
Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT
Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY
30 years residential warranty



3— REGULAR CLEANING: Tarkett Cleaner

4— PERIODICAL CLEANING: Tarkett Refresher

underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

*Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	194
Length (mm)	1123
Wear layer thickness (mm)	~3,6
Boards/pack	6
m ² /pack	1,307
m ² /pallet	65,35
Weight/m ² (kg)	~7,63

design overview



OAK CREAM

OAK ARCTIC BR HG

OAK NATURE

OAK BRANDY

ASH BRANDY

OAK ANTIQUE



ASH COCOA BR

AFRICAN MAHOGANY

ASH SMOKED

OAK GRAPHITE