

Salsa Art

2020

WOOD
product
data
sheet



pattern: 3strip

Creative and artistic collection with enhanced surface structure and colours.

board size: 2283 x 194 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Pure / White	550050015	WHITE PEARL	Ash	Nature	No	Yes	PS(S)	30	Yes	No	No	2702-0005-DoP-2015-08
Essential Brown / Cocoa	550050016	CREAM RHAPSODY	Ash	Thermo/ Cognac	No	Yes	PS(M)	9	Yes	Yes	No	2702-0005-DoP-2015-08
Art Fashion / Line Art	550050014	TOUCH OF GREY	Ash	Rustic	No	Yes	PS(S)	30	Yes	No	No	2702-0005-DoP-2015-08
Art Fashion / Line Art	550050022	WHITE CANVAS	Ash	Nature	Yes	No	PS(S)	30	No	No	No	2702-0005-DoP-2015-08
Art Fashion / Line Art	550050023	BEIGE SUNSHINE	Ash	Rustic	Yes	No	PS(S)	30	No	No	No	2702-0005-DoP-2015-08
Art Fashion / Line Art	550050024	SHADES OF GREY	Oak	Nature	Yes	No	PS(S)	30	No	No	No	2702-0005-DoP-2015-08
Essential Pure / Antique White, Grey	550050026	CHILLED CREAM BR	Oak	Original	Yes	No	PS(M)	9	Yes	No	No	2702-0005-DoP-2015-08
Essential Pure / White	550050027	MOON RIVER	Oak	Original	Yes	No	PS(S)	30	Yes	No	No	2702-0005-DoP-2015-08

PS(S) – Proteco Strong Shiny

PS(M) – Proteco Strong Matt

PS(HG) – Proteco Strong High Gloss

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.

maintenance

- The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1 – WET MOPPING OR VACCUING: Wet mopping with almost dry cloth.
Use protective pads when moving furniture
- 2 – DRY CLEANING: Dry mopping & vacuum cleaning
- 3 – REGULAR CLEANING: Tarkett Cleaner
- 4 – PERIODICAL CLEANING: Tarkett Refresher



T-LOCK
Tarkett lock, glue-free locking system

AQUA GUARD
Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS
Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT
Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY
30 years residential warranty



Protective pads

Tarkett Refresher
Tarkett Cleaner

underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

*Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	194
Length (mm)	2283
Wear layer thickness (mm)	~3,6
Boards/pack	6
m ² /pack	2,658
m ² /pallet	132,9
Weight/m ² (kg)	~7,14

design overview

