

# Tango Art

2020

WOOD  
product  
data  
sheet



pattern: 1 strip

Tango Art collection bring emotions of travelling from all over the world! Each design is carefully made piece of artwork.

board size: 2215 x 164 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Pure / White	550059005	VIOLET TOKYO BR	Oak	UNI Nature	No	Yes	PS(S)	30	Yes	No	Maxi	2702-0005-DoP-2015-08
Essential Pure / White	550059008	WHITE MOSCOW BR	Oak	UNI Rustic	No	Yes	PS(M)	9	Yes	No	Hand	2702-0005-DoP-2015-08
Essential Brown / Cognac	550059002	BROWN BARCELONA BR	Ash	Thermo/ Cognac	No	Yes	PS(HG)	70	Yes	Yes	Hand	2702-0005-DoP-2015-08
Essential Pure / White	550059001	PEARL DUBAI BR	Ash	Nature	No	Yes	PS(S)	30	Yes	No	Maxi	2702-0005-DoP-2015-08
Art Fashion / Rustic Art	550059010	GREY ROME BR	Oak	Nature	Yes	No	PS(S)	30	Yes	No	Maxi	2702-0005-DoP-2015-08
Art Fashion / Rustic Art	550059012	AMBER JOHANNESBURG BR	Oak	UNI Rustic	Yes	No	PS(S)	30	Yes	No	Maxi	2702-0005-DoP-2015-08

PS(S) – Proteco Strong Shiny

PS(M) – Proteco Strong Matt

PS(HG) - Proteco Strong High Gloss

## installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.

## maintenance

– The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1 – WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth. Use protective pads when moving furniture
- 2 – DRY CLEANING: Dry mopping & vaccum cleaning
- 3 – REGULAR CLEANING: Tarkett Cleaner
- 4 – PERIODICAL CLEANING: Tarkett Refresher



### T-LOCK

Tarkett lock, glue-free locking system

### AQUA GUARD

Extended liquid resistance at the short side of boards connection

### HEALTHY FLOORS

Lacquer properties prevent bacteria reproduction

### ENVIRONMENTAL COMMITMENT

Environmental responsibility throughout

all processes ( C2C, FSC, ISO14001)

### WARRANTY

30 years residential warranty



# underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

\*Not suitable for the wood species beech and maple

## technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m <sup>3</sup>	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

## size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	164
Length (mm)	2215
Wear layer thickness (mm)	~3,6
Boards/pack	6
m <sup>2</sup> /pack	2,18
m <sup>2</sup> /pallet	130,8
Weight/m <sup>2</sup> (kg)	~7,50

## design overview



WHITE MOSCOW BR



PEARL DUBAI BR



VIOLET TOKYO BR



GREY ROME BR



BROWN BARCELONA BR



AMBER JOHANNESBURG BR