

Tango

2020

WOOD
product
data
sheet



pattern: 1 strip

Tango collection brings the finest one-piece wood planks found in nature, designed and crafted with perfection.

board size: 2215 x 164 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Brown / Cognac	550058002	AFRICAN MAHOGANY	A. Mah.	Original	No	No	PS(S)	30	No	No	Mini	2702-0005-DoP-2015-08
Essential Brown / Cognac	550058004	ASH COGNAC BR	Ash	Thermo/ Cognac	No	No	PS(M)	9	Yes	Yes	Maxi	2702-0005-DoP-2015-08
Essential Brown / Cognac	550058005	ASH COGNAC	Ash	Thermo/ Cognac	No	No	PS(S)	30	No	Yes	Mini	2702-0005-DoP-2015-08
Essential Brown / Cocoa	550058017	OAK CUMIN BR	Oak	UNI Rustic	No	Yes	PS(M)	9	Yes	No	Maxi	2702-0005-DoP-2015-08
Essential Brown / Cognac	550058024	OAK JAVA BR	Oak	Thermo/ Cognac	No	No	PS(M)	9	Yes	Yes	Maxi	2702-0005-DoP-2015-08
Vintage / Vintage Dark	550058018	OAK ANTIQUE BR	Oak	UNI Rustic	No	Yes	PS(S)	30	Yes	No	Maxi	2702-0005-DoP-2015-08
Vintage / Vintage Dark	550058029	OAK SCHWARZWALD BR	Oak	UNI Rustic	Yes	No	PS(M)	9	Yes	No	Maxi	2702-0005-DoP-2015-08
Essential Brown/ Mocha	550058034	OAK MOCHA BR	Oak	UNI Rustic	Yes	No	PS(M)	9	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Brown/ Mocha	550058035	OAK COPPER BR	Oak	UNI Rustic	Yes	No	PS(S)	30	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Pure / White	550058036	OAK AZURE BR	Oak	UNI Rustic	Yes	No	PS(M)	9	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Pure / Ivory, Grey	550058037	OAK ANTIQ WHITE BR	Oak	UNI Rustic	Yes	No	PS(M)	9	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Brown / Cognac	550058045	OAK BOURBON BR	Oak	UNI Rustic	Yes	No	PS(S)	30	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Pure / Antique White, Grey	550058046	OAK MODERN GREY BR	Oak	UNI Rustic	Yes	No	PS(S)	30	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Classic / Nature	550058043	OAK BARON BR	Oak	UNI Nature	No	No	PS(M)	9	Yes	No	Midi	2702-0005-DoP-2015-08
Essential Classic / Nature	550058044	OAK SAVANNA PREMIUM BR	Oak	Premium	No	No	PS(S)	30	Yes	No	Midi	2702-0005-DoP-2015-08

PS(S) – Proteco Strong Shiny

PS(M) – Proteco Strong Matt

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.



T-LOCK

Tarkett lock, glue-free locking system

AQUA GUARD

Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS

Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT

Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY

30 years residential warranty

maintenance

— The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1— WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth.
Use protective pads when moving furniture
- 2— DRY CLEANING: Dry mopping & vacuum cleaning
- 3— REGULAR CLEANING: Tarkett Cleaner
- 4— PERIODICAL CLEANING: Tarkett Refresher



underfloor heating

— Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.

*Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	164
Length (mm)	2215
Wear layer thickness (mm)	~3,6
Boards/pack	6
m ² /pack	2,18
m ² /pallet	130,8
Weight/m ² (kg)	~7,50

design overview



OAK SCANDINAVIAN



OAK AZURE BR



OAK ANTIQUE WHITE BR



OAK MOCHA BR



OAK COPPER BR



OAK ANTIQUE BR



OAK SCHWARZWALD BR



AFRICAN MAHOGANY



ASH COGNAC



ASH COGNAC BR



OAK CUMIN BR



OAK JAVA BR



OAK BOURBON BR



OAK MODERN GREY BR



OAK BARON BR



OAK SAVANNA PREMIUM BR